


Resist-All-Clad[®]

Mesa

ISO 9001:2000 certified

Mesa engineers Resist-All-Clad[®] flexible pipe for storage tank drain systems (water drainage from the floating roof of an aboveground storage tank). Resist-All-Clad is also used in Mesa's skimmer systems (used to separate liquids in the storage tank) and foam delivery systems (used to distribute foam around the storage tank's rim area).

Resist-All-Clad has a smooth inner wall (non turbulent) to ensure optimum flow rates. It is 100% compatible with aromatic storage products and features negative buoyancy in all storage tank products. Resist-All-Clad features a preformed, multiple coil, repeating lay pattern which prevents the flexible pipe from sliding on the tank floor as the roof raises or lowers. The flexible pipe features



a tether system that keeps it in position as installed. One tether is welded to the underside of the floating roof. Standard Resist-All-Clad specifications operate in temperatures ranging from -40° to 180° F. Specifications are available for higher temperature applications. Resist-All-Clad suffers no damage from freezing. The flexible pipe is cold weather tested and certified.

Resist-All-Clad features a steel exterior "armor" for protection during installation and service. This protective exterior has a low coefficient of friction.

www.mesarubber.com/resist-all-clad.htm

1726 South Magnolia Avenue
Monrovia, CA 91016-4595
Phone: 626.359.9361
Fax: 626.359.7985

9202 Meadow Vista Boulevard
Houston, TX 77064-2012
Phone: 281.469.8098
Fax: 281.469.9524

4141 Airport Road
Cincinnati, OH 45226-1643
Phone: 513.321.4511
Fax: 513.321.8178